

K5S Vacuum chamber machine

Technical data sheet

The compact performance for efficient packaging

Cost-effective, easy to operate, space-saving and designed overall for hygiene. This mobile free-standing model has been operating reliably for years and packs the most diverse products in bags. Whether you're a butcher or an industrially equipped fruit or vegetable processor – you can be sure that all products are securely packed. The K5S processes the desired production volume with high reliability – even in harsh production environments.



Facts

Usable chamber size	695 x 480 x 205 mm *
External dimensions without panel	939 x 969 x 1074 mm *
Welding strip lengths	695 mm / 480 mm
Weight with pump	348 kg
Machine cycle	up to 3 cycles / min
Electrical connection	400 V / 3 / 50 Hz / 4 kW **
Compressed air	no
Vacuum pump	106 m ³ /h
Welding and detachable technology	from above counter strip below
Pre-ventilation (soft ventilation)	standard
Evaporation point sensor (H ₂ O sensor)	standard
MAP (inert gas option)	optional
Filler plates	standard
Automatic lid	no
Types of evacuation	up to evaporation up to setpoint in steps up to setpoint timed (emergency operation)
Trolley	yes
Bag residue extraction	no



Usable product area



* Width x depth x height
** Voltage variants on request
Subject to technical changes

K55 Vacuum chamber machine:



Hygienic design
Easy operation
Service-friendly

Wireless, click-in welding strips
are built into the lid

Automatic cycle start on manually
closing the lid

Multilingual user interface

Raised suction socket in the chamber lid

Password protection for
stored recipes (programs)

Separately controllable
welding and detachable seam

Evaporation point recognition,
staged vacuuming, intermediate
ventilation, pre-ventilation:
Energy cost savings and maximum
product quality

No compressed air required to
operate the machine

Trolley



Options & accessories

1. VC999 chamber machines are also available with modified atmosphere packaging
2. Insert for the packaging of liquids
3. Pump mounted externally to reduce noise, odour and heat
4. Extension to manual shrink line
5. Filling shovel



Packaging material | The right bag for the customer's every need

